

MR-11 SERIES


Only for Use in Approved Halogen Fixtures

12 Volt, Average Life 2,000 Hours


Optional Beam Angle

Watts	Item code	Description	Voltage (V)	CBCP (cd)	Beam Angle	Avg.Life (Hours)	Color Temp (K)	Case Qty.
12 Volt, Miniature 2-Pin Base - GU4 Without Cover								
20	H02011610001	MR11 FTB	12	3000	10°	2000	2925	20
20	H02011620001	MR11 FTC	12	1500	20°	2000	2925	20
20	H02011630001	MR11 FTD	12	600	30°	2000	2925	20
35	H03511610001	MR11 FTE	12	6000	10°	2000	2950	20
35	H03511620001	MR11 FTF	12	2400	20°	2000	2950	20
35	H03511630001	MR11 FTH	12	1300	30°	2000	2950	20
12 Volt, Miniature 2-Pin Base - GU4 With Cover								
20	H02011610101	MR11 FTB/C	12	3000	10°	2000	2925	20
20	H02011620101	MR11 FTC/C	24	1500	20°	2000	2925	20
20	H02011630101	MR11 FTD/C	12	600	30°	2000	2925	20
35	H03511610101	MR11 FTE/C	12	6000	10°	2000	2950	20
35	H03511620101	MR11 FTF/C	12	2400	20°	2000	2950	20
35	H03511630101	MR11 FTH/C	12	1300	30°	2000	2950	20

All measurements are shown in inches unless noted



MaxØ=1.36"



MR11/GU4



GU4