



FL4-SERIES MULTI-MOUNT FLOOD LIGHT



Project	
Date	
Prepared by	
Model #	FL4-804T5-1

OVERVIEW

The FL4-Series Flood Light represents our entry into specification grade exterior lighting. Finished in black, its sleek design and larger housing size provides an attractive look, especially when mounted on poles. Offering a wide range of mounting options, lumen packages, IES beam distribution patterns, and integrated controls, they will allow you to achieve any design requirement.

PRODUCT HIGHLIGHTS

- Interchangeable mounting options to adapt to any application: yoke, trunnion, slip fitter or mounting arm*
- Operates in -40°F/-40°C degree outdoor weather
- 1-10V dimming for maximum control and energy savings
- IP65 and Wet Location rated
- Black contemporary finish to complement all outdoor environments
- Available with integrated motion sensor or photocell (optional)

*Fixture does not include mount. Mount must be ordered separately.



OPTICAL SPECIFICATIONS

Lumen Output (lm) ₁	11137 lm	Beam Angle (°) ₁	Type V (125°x160°)
CCT (K) ₁	4000K	Projected Lifetime (L ₇₀)	50,000 hrs
CRI (Ra) ₁	80	Chromaticity Shift	±250K
Efficacy (lm/W) ₁	135 lm/W		

ELECTRICAL SPECIFICATIONS

Power	80W	Replacement For	Up to 250W HID
Apparent Power (VA)	81.5VA	Current Draw at 120V _{AC} (A) ₂	0.672A
System Wattage (W)	82.23W	Current Draw at 208V _{AC} (A) ₂	0.437A
Input Voltage	100-277VAC	Current Draw at 240V _{AC} (A) ₂	0.348A
Output Voltage (VDC)	56VDC	Current Draw at 277V _{AC} (A) ₂	0.292A

PRODUCT DIMENSION



CONSTRUCTION

Housing Material	Aluminum Alloy	Installation Method	Wall Mounted/ Square Pole Mounted/ Round Pole Mounted
Housing Color	Black	Operation Range (°F/°C)	-40°F to 113°F/-40°C to 45°C
Lens Material	Polycarbonate	Weight (Kg/Lbs)	6.7kg / 14.77lbs
Dimensions (inch/mm)	15.3" x13.4" x 4.3" / 389mm x 342mm x 109mm	Warranty	10 Years


APPROVALS AND LISTINGS

DLC Premium	PFEIEQEY	IP Rating	IP65
Wet Location Rated	Yes	EPA Rating	1.89 ft²
UL/ETL	cETLcus	BUG Rating	B3-U2-G2

LED AND DRIVER SPECIFICATIONS

LED Type	3030	Surge Protection	L/N-PE: 10KV, L-N: 6KV
Dimmable	Yes (1-10V)	Inrush Current (A)	80A/180A
Power Factor	0.9	Driver Class	Class 2
THD	15%		

PHOTOMETRICS



ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LAMP	% LUMINAIRE
0-30	971.9	8.7%	8.7%
0-40	1,990.1	17.9%	17.9%
0-60	5,980.1	53.7%	53.7%
60-90	5,116.5	45.9%	45.9%
70-100	2,074.4	18.6%	18.6%
90-120	25.0	0.2%	0.2%
0-90	11,096.6	99.6%	99.6%
90-180	40.9	0.4%	0.4%
0-180	11,137.4	100%	100%

LCS TABLE

BUG RATING

B3 - U2 - G2

FORWARD LIGHT

LUMENS LUMENS %

LOW(0-30): 456.4 4.1%

MEDIUM(30-60): 2,211.4 19.9%

HIGH(60-80): 2,532.7 22.7%

VERY HIGH(80-90): 160.9 1.4%

BACK LIGHT

LOW(0-30): 515.4 4.6%

MEDIUM(30-60): 2,797.2 25.1%

HIGH(60-80): 2,381.3 21.4%

VERY HIGH(80-90): 41.1 0.4%

UPLIGHT

LOW(90-100): 8.5 0.1%

HIGH(100-180): 32.4 0.3%

TRAPPED LIGHT: 0.0 0%

ILLUMINANCE AT A DISTANCE

HEIGHT(FT)	CENTER BEAM	BEAM SPREAD(FT)		FIELD SPREAD(FT)	
	FOOTCANDLE	HORIZONTAL	VERTICAL	HORIZONTAL	VERTICAL
4.00	61.08 FC	12.9	26.1	22.0	44.0
8.00	15.27 FC	25.8	52.2	44.1	88.0
12.00	6.79 FC	38.7	78.4	66.1	132.0
16.00	3.82 FC	51.6	104.5	88.1	176.0
20.00	2.44 FC	64.5	130.6	110.2	220.0
		BEAM ANGLE		FIELD ANGLE	
		116.4°	145.9°	140.1°	159.4°

MOUNTING OPTIONS

	FL-MA4	Mounting Arm for FL4-Series Area/Flood Lights		FL-SF4	Slip Fitter for FL4-Series Area/Flood Lights
	FL-TR4	Trunnion Mount for FL4-Series Area/Flood Lights		FL-YK4	Yoke Mount for FL4-Series Area/Flood Lights

ACCESSORIES

	PC1-TPT-1	Stem Mount Swivel Photocell (Compatible with Mounting Arm or Slip Fitter option only)		FL-SHIELD14	Glare Shield for FL4-Series Area/Flood Lights (80W/100/150W models only)
---	------------------	---	---	--------------------	--

PRODUCT KEY

FL4

-

-

-

Adders

Product Series

CCT

Voltage

Wattage

LENS

☐ 4 - 4000K

☐ 1 - 100-277V
☐ 2 - 277-480V

☐ 80
☐ 100
☐ 150
☐ 200
☐ 240
☐ 300
☐ 450

☐ T3 - Type III Distribution
☐ T4 - Type IV Distribution
☐ T5 - Type V Distribution

Example

FL4-2404T3-1-M6P1

FACTORY INSTALLED ADDERS

Motion Sensor Adders

☐ M6 Microwave Motion Sensor, Dimmable, 120-277V (80W-300W models)
☐ M7 Microwave Motion Sensor, Dimmable, 120-277V (450W model)

Photocell Sensor Adders

☐ P1 Stem Mount Photocell, 120V (Mounting Arm and Slip Fitter Only)

1. Due to the special conditions of manufacturing, the typical data of optical specifications can only reflect statistical figures and do not necessarily correspond to the actual parameters of each single product which could differ from the typical data.
 2. Exceeding maximum ratings for input voltage and current will cause hazardous overload and will likely destroy the LED fixture.
 3. Refer to Warranty Terms & Conditions available at premiseled.com/warranty