

Date:	Project Name:
Type:	Part Number:



## T5 TYPE C



### FEATURES

- Direct plug-in & Safe Installation
- No UV or IR radiation
- High luminous efficiency
- Compatible with any Type C Driver and Reno's Dali Driver
- CRI >83
- Operating temperature: -4°F to +113°F (-20°C to +45°C)
- Dimming based on Driver parameters
- Suitable for dry/damp locations
- Suitable for open fixtures
- CRI >83
- Rated Lifetime L70(hrs): >50,000
- 5 year warranty

### APPLICATIONS

- Food Service Equipment
- Office Lighting
- Residential



Date:	Project Name:
Type:	Part Number:

## SPECIFICATION

ORDER#	MODEL#	WATTS	SIZE	EFFICACY	LUMENS	BASE TYPE	BEAM ANGLE	CCT (K)
R42202	RENO-LEDT5EX13W-MCCT	13W	4FT	138 lm/W	1800 lm	G5	330°	30/35/40/50/65K
R42203	RENO-LEDT5EX25W-MCCT	25W	4FT	136 lm/W	3400 lm	G5	330°	30/35/40/50/65K

## ACCESSORIES OPTIONS

ORDER#	MODEL#	DESCRIPTION
R83101	RENO-DA54B-DV-PS	LED Iso adjustable power Driver



RENO-DA54B-DV-PS

## DIMENSIONS

4FT

