

Date:	Project Name:
Type:	Part Number:



BUILT IN  
MICROWAVE SENSOR  
For some models



# SABRE SERIES

## LED ECO LINEAR STRIP MS

### DESCRIPTION

Reno Lighting's Sabre Series LED ECO Commercial Strip fixture features a polycarbonate diffuser that provides impact resistance and even light distribution while emitting low glare. Combine this with powerful, high-output LED chips, these fixtures meet today's stringent efficacy standards, bringing your projects maximum energy savings while providing exceptional light levels! With our new built-in Microwave dimming sensor we take your energy savings a step further by giving you: stand-by dimming, daylight harvesting, occupancy/vacancy settings coupled with high level trimming!

### FEATURES

- DLC Premium for the Stairwell and Passageway Luminaires
- 0-10V dimming control compatible
- Surface or Suspension mounting options
- Operating temperature: -22°F to +122°F (-30°C to +50°C)
- Dual Voltage 120-347V
- Frosted Polycarbonate Lens
- Integrated microwave sensor
- Suitable for Damp Location
- CRI >80
- Rated Lifetime L70(hrs): >70,000
- Includes J-Box Coverplate and V-Hangers
- Multi CCT & Wattage
- 5 year warranty

### APPLICATIONS

-  Parking Garage
-  Stairwell / Passageway
-  Warehouse



Date:	Project Name:
Type:	Part Number:

## SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	CCT (K)	LUMENS	EFFICACY	CRI
R33024	RENO-LSN4-DV-MCCT-MW-ECO-MS	20W	120-347V	3500K	2460 lm	123 lm/W	>80
		30W			3660 lm	122 lm/W	
		40W			4836 lm	120.9 lm/W	
		20W		4000K	2720 lm	136 lm/W	
		30W			4050 lm	135 lm/W	
		40W			5360 lm	134 lm/W	
		20W		5000K	2500 lm	125 lm/W	
		30W			3720 lm	124 lm/W	
		40W			4920 lm	123 lm/W	
R33025	RENO-LSN8-DV-MCCT-MW-ECO-MS	40W	120-347V	3500K	4920 lm	123 lm/W	>80
		60W			7320 lm	122 lm/W	
		80W			9554 lm	119.4 lm/W	
		40W		4000K	5440 lm	136 lm/W	
		60W			8100 lm	135 lm/W	
		80W			10,720 lm	134 lm/W	
		40W		5000K	5000 lm	125 lm/W	
		60W			7440 lm	124 lm/W	
		80W			9840 lm	123 lm/W	

## DLC INFORMATION

ORDER#	MODEL#	APPLICATION	DLC	
			STANDARD	PREMIUM
R33024	RENO-LSN4-DV-MW-MCCT-ECO-MS	Direct Linear Ambient Luminaires	P08KVTQ4	
		Stairwell and Passageway Luminaires		S-M9R7UG
R33025	RENO-LSN8-DV-MW-MCCT-ECO-MS	Direct Linear Ambient Luminaires	P7SRLY9D	
		Stairwell and Passageway Luminaires		S-QJUBNX

Date:	Project Name:
Type:	Part Number:

## ACCESSORIES OPTIONS

ORDER#	MODEL#	DESCRIPTION
R39307	I-BRACKET	I-Bracket for straight continuous Installation
R83004	RENO-EM-C08	Emergency LED Driver



I-BRACKET



RENO-EM-C08

## REMOTE OPTIONS

ORDER#	MODEL#	DESCRIPTION
R73002	RENO-REMOTE-H	Controller for Bi-Level Sensor
R73005	RENO-REMOTE-H-ECO	ECO Remote (without screen)




RENO-REMOTE-H



RENO-REMOTE-H-ECO

Date:	Project Name:
Type:	Part Number:

## DIMENSIONS



53.3mm  
(2.1")

4FT



1219.2mm (48")



8FT



2438.4mm (96")

