

Date:

Type:

Project Name:

Part Number:

Ballast-compatible LED T8 TUBE (Type A) 4FT (High Efficiency)



FEATURES

- Direct plug-in & Safe Installation
- No UV or IR radiation
- High luminous efficiency
- Compatible with instant & programmed start ballast
- Operating Temperature: -20°c to 45°c
- 50,000⁺ hours lifespan (L70)
- 5 Year Warranty

APPLICATIONS

- Office Lighting
- Commercial Applications
- Retail Lighting
- Residential

SPECIFICATION

ORDER#	MODEL #	LENGTH	WATTS	BASE	VOLTAGE(V)	HOUR RATING	BEAM ANGLE	INITIAL LUMENS	CCT(K)	CRI
R41020	WLL-LEDT8BC13/840/HE	4'	13W	G13	BF	50,000	320°	2200	4000K	83+
R41021	WLL-LEDT8BC13/850/HE	4'	13W	G13	BF	50,000	320°	2200	5000K	83+
R41024	WLL-LEDT8BC9/840/HE	4'	9W	G13	BF	50,000	320°	1800	4000K	83+
R41025	WLL-LEDT8BC9/850/HE	4'	9W	G13	BF	50,000	320°	1800	5000K	83+
R41023	WLL-LEDT8BC10/850/HE	4'	10W	G13	BF	50,000	320°	1800	5000K	83+
R41026	WLL-LEDT8BC10/830/HE	4'	10W	G13	BF	50,000	320°	1700	3000K	83+

DIMENSIONS

■ 4FT

