

Date:	Type:
Project Name:	Part Number:

ECO-BYPASS /Line Voltage LED T8 Tube (Type B)



FEATURES

- Built-in safety switch prevents electrical shock during installation
- Operates directly on 120-277V line voltage
- Simple ballast bypass, Double ended power
- Compatible with shunted and non-shunted lamp holders
- Rated for use in fully enclosed fixtures.
- Suitable for use in dry and damp locations.
- NSF Listed: NSF/ANSI Standard 2 - Food Equipment
- Operating Temperature: -20°C/-4°F to 45°C/113°F
- 50,000+ Hour Lifetime (L70)
- 7 Year Warranty
- Reno LED T8 lamps conform to UL 1598 Standard

APPLICATIONS

- Office Lighting
- Commercial Applications
- Residential



Shatterproof

SPECIFICATION

ORDER #	MODEL #	SIZE	WATTS	BASE	VOLTAGE(V)	HOUR RATING	BEAM ANGLE	INITIAL LUMENS	CCT(K)	CRI
R41130	WLL-LEDT8BP12/840-ECO(4FT)	4'	12W	G13	120-277V	50,000	330°	1800	4000K	83+
R41131	WLL-LEDT8BP12/850-ECO(4FT)	4'	12W	G13	120-277V	50,000	330°	1800	5000K	83+



Date:	Type:
Project Name:	Part Number:

RENO GLASS VS PLASTIC

Plastic Tube



RENO Glass



DIMENSIONS

