

Project Name

Location

Prepared By



## SATCO 67-121

EXIT/LIGHT DH - RED

### Notes

[www] 06-25-2023 04:02:53

### General

|                           |           |
|---------------------------|-----------|
| Status                    | Active    |
| Fixture Type              | Exit Sign |
| Finish                    | White     |
| Wattage                   | 2.8W      |
| Lumen Output              | 150L      |
| CCT (Kelvin)              | 5700K     |
| Indoor or Outdoor Fixture | Indoor    |

### Specifications

|                       |                             |
|-----------------------|-----------------------------|
| Technology            | LED                         |
| CRI                   | 70                          |
| Voltage               | 120V/277V                   |
| Operating Temperature | +10C (+50F) to +40C (+104F) |
| Dimmable              | Non-Dimmable                |
| Lens Material         | Polycarbonate (PC)          |
| Weight (lb.)          | 2.99                        |
| Material              | Thermoplastic               |

### Dimensions

|              |      |
|--------------|------|
| Height (in.) | 7.25 |
| Width (in.)  | 19   |
| Length (in.) | 4    |

### Compliance

|                        |                                     |
|------------------------|-------------------------------------|
| Safety Listing         | cULus - Certified                   |
| Location Rating        | Damp                                |
| Energy Star            | No                                  |
| CA T20 / T24 Rationale | T20 Exempt - Fixtures Not Regulated |
| California Status      | Lawful for sale in California       |
| Title 20 / 24 Status   | Lawful for sale                     |
| California Prop 65     | Lead                                |
| RoHS Compliant         | Yes                                 |
| FCC Compliant          | Yes                                 |

### Additional Information

|                        |                                                                                                                                                                              |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional Information | Input Wattage: 2.8W; Output Wattage: 1.5W; Energy Used in Maintenance Mode: 2.8W                                                                                             |
| Specification Note     | UL94V-0, Thermoplastic, 3.6V AA900mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in.; Letter Stroke: 0.75 in.; Path of Egress: 6 Ft |
| Includes               | Mounting hardware and accessories                                                                                                                                            |
| Warranty               | 2 Year Limited                                                                                                                                                               |