

Project Name

Location

Prepared By



SATCO S11937

11T8/LED/36-850/XD

Notes

General

Status	Active
Watts	11
Fluorescent Equivalent	25
Volts	120V-277V
Ballast Type	Type C
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	36
Finish	Frosted
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	82
Lumens	1600
Beam Spread	220
Dimmable	0-10V Dimming Only
Hours Rated	50000
Technology	LED

Electrical

Ballasting Requirements	Ballast replaced with external driver
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	36
MOD	1
Weight (lb.)	0.34

Additional Information

Additional Info	Not for emergency lighting
Tube Guard Use	Approved for use with tube guards
Warranty	5 Year Limited

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLRWRJ8NB39P
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

