

Project Name

Location

Prepared By



SATCO S11940

12T8/LED/48-840/XD

Notes

General

Status	Active
Watts	12
Fluorescent Equivalent	32
Volts	120V-277V
Ballast Type	Type C
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	4000
Temperature	Cool White
CRI	82
Lumens	1800
Beam Spread	220
Dimmable	0-10V Dimming Only
Hours Rated	50000
Technology	LED

Electrical

Ballasting Requirements	Ballast replaced with external driver
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	48
MOD	1
Weight (lb.)	0.44

Additional Information

Additional Info	Not for emergency lighting
Tube Guard Use	Approved for use with tube guards
Warranty	5 Year Limited

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLR2T3SDBRJX
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

