

Project Name

Location

Prepared By



SATCO S11955

30T8/LED/70-840/BP

Notes

[www] 03-22-2021 04:50:55

General

Status	Active
Watts	30
Fluorescent Equivalent	70W
Volts	120-277
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	70
Finish	Frosted
CCT (Kelvin)	4000
Temperature	Cool White
CRI	83
Lumens	4000
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
THD	0.25
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	70
MOD	1
Material	glass
Lens Finish	frosted
Lens Material	glass
Housing Color	White
Weight (lb.)	0.5

Additional Information

Tube Guard Use	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cRUus; cULus Classified; ETL Listed
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale in California
RoHS Compliant	Yes
FCC Compliant	Yes

NSF Approved

Yes

