

Project Name

Location

Prepared By



SATCO S16411

36T8/LED/HO-SIGN/96-865/BP

Notes

General

Status	Active
Watts	36
Fluorescent Equivalent	113
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	96
Finish	Frosted
CCT (Kelvin)	6500
Temperature	Daylight
CRI	83
Lumens	5000
Beam Spread	330
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Dimmable Down To	N/A
Dimming Type	N/A
Power Factor	0.9
Operating Temperature	-30C (-22F) to a maximum of +45C (+113F)

Physical

MOL	93.88
MOD	1

Additional Information

Installation Notes	No ballast or external driver required; Direct wire 120-277V line voltage; Single ended wiring
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass - Outdoor Temperature Rated

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	Yes - Approved

