SATCO NUVO

Project Name

Location Prepared By



N		ta	
LX.	u	w	E

[www] 05-15-2024 04:42:

Status	Active	
Watts	11W	
Fluorescent Equivalent	22W	
Volts	120V-277V	
Ballast Type	Type A/B	
Shape	T9	
Base	G10q (4-Pin)	
ANSI Base	G10q	
Finish	Frost	
CCT (Kelvin)	3000K/4000K/6500K	
Temperature	Soft White to Daylight	
CRI	80+	
Lumens	1300L/1400L/1350L	
Beam Spread	180	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	Circline	
Technology	LED	
Electrical		
Ballasting Requirements	Ballast required (Type A, Electronic only) or Ballast Bypass (Type B)	
Operating Frequency	50/60Hz	
THD	25%	
Operating Temperature	-20C (-4F) to +45C (+113F)	
Physical		
MOD	8.08	
Housing Color	Frost	
Weight (lb.)	0.37	
Additional Information		
	Only compatible with Electronic ballasts when installed in Type A	
Specification Note	mode. See ballast compatibility list for details. Not for use on magnetic ballasts.; Inner Diameter: 5.71 in.	
Specification Note Installation Notes	mode. See ballast compatibility list for details. Not for use on magnetic	
	mode. See ballast compatibility list for details. Not for use on magnetic ballasts.; Inner Diameter: 5.71 in.	

Warranty	5 Year Limited - 10 hr per day
Compliance	
Safety Listing	cETLus - Classified
Location Rating	Damp
Energy Star	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes

