

Project Name

Location

Prepared By



## SATCO S21760

10T8/LED/24-5CCT/DM/BP-DR

### Notes

(www) 12-02-2024 01:00:35

### General

|                        |                               |
|------------------------|-------------------------------|
| Status                 | Active                        |
| Watts                  | 10W                           |
| Fluorescent Equivalent | 15W/17W                       |
| Volts                  | 120V-277V                     |
| Ballast Type           | Type A/B                      |
| Shape                  | T8                            |
| Base                   | Medium Bi Pin                 |
| ANSI Base              | G13                           |
| Nominal Length         | 24                            |
| Finish                 | Frost                         |
| CCT (Kelvin)           | 3000K/3500K/4000K/5000K/6500K |
| Temperature            | Soft White to Daylight        |
| CRI                    | 80+                           |
| Lumens                 | 1450L                         |
| Beam Spread            | 170                           |
| Dimmable               | Yes-Dimmable                  |
| Hours Rated            | 50000                         |
| Product Category       | Linear                        |
| Technology             | LED                           |

### Electrical

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Ballasting Requirements | Ballast required (Type A) or Ballast Bypass (Type B)            |
| Operating Frequency     | 50/60Hz                                                         |
| Dimming Note            | Only in Type A mode; Check Ballast MFG for Dimmer Compatibility |
| Power Factor            | 0.9                                                             |
| THD                     | 20%                                                             |
| Operating Temperature   | -20C (-4F) to +45C (+113F)                                      |

### Physical

|              |       |
|--------------|-------|
| MOL          | 24.65 |
| MOD          | 1     |
| Material     | Glass |
| Weight (lb.) | 0.27  |

### Additional Information

|                            |                                      |
|----------------------------|--------------------------------------|
| Shatter-Proof Type         | PET Coated                           |
| Installation Notes         | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes                                  |
| Warranty                   | 5 Year Limited - T8 LED Bulbs        |

### Compliance

|                        |                                                       |
|------------------------|-------------------------------------------------------|
| Safety Listing         | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating        | Damp                                                  |
| DLC Approved           | Yes                                                   |
| DLC ID                 | S-KYQNVV                                              |
| CA T20 / T24 Rationale | Exempt - Base Not Regulated                           |
| California Status      | Lawful for sale in California                         |
| Title 20 / 24 Status   | Lawful for sale                                       |
| RoHS Compliant         | Yes                                                   |
| FCC Compliant          | Yes                                                   |
| NSF Approved           | Yes                                                   |