



S29927

12T8/LED/36-835/BP 120-277V
12 watt T8 LED; Medium bi-pin base; 3500K; 50000 Average
rated hours; 1400 lumens

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29927

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29927	045923299278	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin

ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-835/BP 120-277V	Non-Dimmable	White	36"	1.00"	1400	50000

Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status
3500	Neutral White	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Box	Lawful for sale in California

DLC ID:	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
PLZCLRCISTTC DLC Search	Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051