SATCO NUVO

Project Name

Location

Prepared By



SATCO S39390

18W/LED/HID/5000K/100-277V E26

Notes

| Conoral | |
|---|--|
| General | |
| Status | Active |
| Watts | 18 |
| Incandescent Equivalent | 120 |
| Fluorescent Equivalent | 32 |
| HID Equivalent | 70 |
| Volts | 100V-277V |
| Shape | Corncob |
| Base | Medium |
| ANSI Base | E26 |
| Finish | Un-Lensed |
| CCT (Kelvin) | 5000 |
| Temperature | Natural Light |
| CRI | 80 |
| Lumens | 2610 |
| Beam Spread | 300 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Corncob |
| Technology | LED |
| Min Compartment Size | Length 6 in. Width 8.5 in. Depth 6 in. |
| Ballasting Requirements | Ballast by-pass - Direct wire only 100 - 277V |
| Electrical | |
| | |
| | AC 90-305V |
| Working Voltage | AC 90-305V |
| Working Voltage Operating Frequency | 50/60 Hz |
| Working Voltage Operating Frequency Dimmable Down To | 50/60 Hz N/A |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type | 50/60 Hz N/A N/A |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor | 50/60 Hz N/A N/A >0.9 |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position | 50/60 Hz N/A N/A >0.9 Universal |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical MOL | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) 5.69 2.38 |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) 5.69 2.38 Clear |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material | 50/60 Hz N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) 5.69 2.38 Clear Plastic |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color | 50/60 Hz N/A N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) 5.69 2.38 Clear Plastic White |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) | 50/60 Hz N/A N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) 5.69 2.38 Clear Plastic White 0.68 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information | 50/60 Hz N/A N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) 5.69 2.38 Clear Plastic White 0.68 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) |
| Working Voltage Operating Frequency Dimmable Down To Dimming Type Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information | 50/60 Hz N/A N/A N/A >0.9 Universal Built-in surge protection - 2.5KV -20C (-4F) to a maximum of +40C (+104F) 5.69 2.38 Clear Plastic White 0.68 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no |









| Compliance | |
|-----------------|-------------------------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | No |
| CEC Status | Lawful for sale in California |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |







