

Project Name

Location

Prepared By



## SATCO S39391

22W/LED/HID/5000K/100-277V E26

### Notes

### General

Status	Active
Watts	22
Incandescent Equivalent	150
Fluorescent Equivalent	40
HID Equivalent	100
Volts	100V-277V
Shape	Comcob
Base	Medium
ANSI Base	E26
Finish	Un-Lensed
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80
Lumens	3080
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Comcob
Technology	LED
Min Compartment Size	Length 8.5 in. Width 6 in. Depth 6 in.
Ballasting Requirements	Ballast by-pass - Direct wire only 100 - 277V

### Electrical

Working Voltage	AC 90-305V
Operating Frequency	50/60 Hz
Dimmable Down To	N/A
Dimming Type	N/A
Power Factor	>0.9
Burning Position	Universal
Surge Protection	Built-in surge protection - 2.5KV
Operating Temperature	-20C (-4F) to a maximum of +40C (+104F)

### Physical

MOL	5.69
MOD	2.38
Lens Finish	Clear
Lens Material	Plastic
Housing Color	White
Weight (lb.)	0.7

### Additional Information

Additional Info	UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)
Enclosure Rating	Enclosed Rated Lamp
IP Rating	IP64
Warranty	5 Year Limited - Hi-Pro

## Compliance

Safety Listing	cULus
Location Rating	Damp
Energy Star	No
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

