

Project Name

Location

Prepared By



## SATCO S39750

30W/LED/HID/MB-G3/50K/100-277V

### Notes

[www] 09-21-2020 03:40:10

### General

|                         |                                                      |
|-------------------------|------------------------------------------------------|
| Status                  | Active                                               |
| Watts                   | 30                                                   |
| Incandescent Equivalent | 200                                                  |
| Fluorescent Equivalent  | 55                                                   |
| HID Equivalent          | 150                                                  |
| Volts                   | 100V-277V                                            |
| Shape                   | Comcob                                               |
| Base                    | Medium                                               |
| ANSI Base               | E26                                                  |
| Finish                  | Clear                                                |
| CCT (Kelvin)            | 5000                                                 |
| Temperature             | Natural Light                                        |
| CRI                     | 80                                                   |
| Lumens                  | 4200                                                 |
| Beam Spread             | 120;150;260                                          |
| Dimmable                | Non-Dimmable                                         |
| Hours Rated             | 50000                                                |
| Lamp Type               | LED HID                                              |
| Technology              | LED                                                  |
| Min Compartment Size    | Width: 8.00 in. Depth: 8.00 in.<br>Height: 11.00 in. |

### Electrical

|                       |                                            |
|-----------------------|--------------------------------------------|
| Operating Frequency   | 50/60 Hz                                   |
| Surge Protection      | Built-in surge protection - 4KV            |
| Operating Temperature | -20C (-4F) to a maximum of +65C<br>(+149F) |

### Physical

|               |                 |
|---------------|-----------------|
| MOL           | 6.69            |
| MOD           | 3.35            |
| Housing Color | White           |
| Photocell     | Optional Add-On |
| Weight (lb.)  | 1.37            |

### Additional Information

|                            |                                                  |
|----------------------------|--------------------------------------------------|
| Additional Info            | PIR Sensor available as an accessory             |
| Enclosure Rating           | Enclosed Rated Lamp                              |
| Rated For Enclosed Fixture | Yes                                              |
| IP Rating                  | IP64                                             |
| Specification Note         | Closed 260 deg; Partial 150 deg;<br>Open 120 deg |
| Warranty                   | 5 Year Limited - Hi-Pro                          |

### Compliance

|                 |                               |
|-----------------|-------------------------------|
| Safety Listing  | cULus Classified              |
| Location Rating | Damp                          |
| Energy Star     | No                            |
| CEC Status      | Lawful for sale in California |

|                |          |
|----------------|----------|
| RoHS Compliant | Yes      |
| SDS Sheet      | LED_Lamp |