

Project Name

Location

Prepared By



SATCO S8892

13T8/LED/48-840/DUAL/BP-DR

Notes

General

Status	Active
Watts	13
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	4000
Temperature	Cool White
CRI	83
Lumens	1900
Beam Spread	240
Dimmable	Non-Dimmable in Bypass Mode
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast bypass (Type B)
Operating Frequency	50/60 Hz
Power Factor	0.96
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	48
MOD	1
Housing Color	White

Additional Information

Additional Info	Do not use with dimmers in by-pass mode. Check the ballast for dimming capability when using with a ballast.
Specification Note	Ballast Compatible - bare lamp is 12W; Ballast Bypass - 13W. Protection from arcing- Power must be turned off prior to installing lamps. Sockets must be in good working order, not broken, cracked or electrically compromised. If arcing occurs at the l
Warranty	5 Year Limited

Compliance

Safety Listing	cULus Listed for Type A; cULus Classified for Type B
Location Rating	Damp
Energy Star	No
DLC Approved	Yes

DLC ID	PLIR7BJW4P8T
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	Yes - Approved