

Project:



Thin-Line LED Wall Bar Spec Sheet

SKU: 2812.03-4-27

One of our best selling families, Thin-Line is a system of minimally scaled LED wall bars, [indirect light wall bars](#), and [pendants](#). Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. One-sided configurations direct light in a single direction, and can be mounted in an uplight or downlight orientation. Two-sided configurations direct light both up and down.

Learn more: <https://sonnemanlight.com/thin-line-led-wall-bar>

Type #:



Dimensions

Height:	1"
Width:	48"
Extends:	3.5"
Minimum Extension:	3.5"
Maximum Extension:	3.5"
Size:	4' Two-Sided

Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	2
Input Voltage:	120VAC
Wattage:	44
Initial Lumens:	2910
Delivered Lumens:	1800
Kelvin:	2700K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	2
Power Supply Location:	Remote
Dimming Type:	TRIAC/ELV

Installation

Installation:	Licensed electrician required
Sloped Ceiling Compatible?:	Adapter Available up to 45°
Installation Orientation:	Any Orientation

Shipping

Carton 1 L x W x H:	51" X 7" X 4"
Carton 1 Gross Weight:	5 LBS

Shade

Shade Material:	Aluminum w/Optical Acrylic
-----------------	----------------------------

General Listings

Features:	At NYDC, Damp Rated
Certification:	C-ETL-US
Color/Finish:	Satin White (.03)

Available Finishes

Available Finishes:	Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)
---------------------	---

Available Color Temperatures

Available Color Temperatures:	2700K, 3000K, 3500K
-------------------------------	---------------------