



General Purpose Strip T8/T5

DESCRIPTION

The General Purpose Strip's full body assembly accommodates multiple optics utilizing either T5 or T8 lamps. The heavy-duty 20 gauge housing is code gauge steel, and all components are post painted with a glossy, high reflectance white paint. Sockets include secure, positioning rotating collars.

APPLICATION

The General Purpose Strip is designed for surface or suspended mounting. The fixture is ideal for medium illumination levels and suitable for general task lighting. Suggested use for mounting heights up to 16' requiring low to medium light levels. Ideal for light-duty task lighting, aisles, warehousing, storage and retail.

REFLECTOR OPTICS

The General Purpose Strip is available using a specular aluminum (SA) Miro®4 or a white aluminum (WA) ballast cover, which have a 25 year warranty.

ELECTRICAL

All ballasts are Class P rated and UL/cUL Listed. Our ballasts are also thermally protected, sound rated and tightly secured by mounting bolts, as well as NEMA Premium and CEE qualified.

FINISH

The baked white enamel finish is electrostatically applied and post painted with a glossy, highly reflective and durable white paint.



ARRA Qualified

General Purpose Strip T8 & T5 Series

MAINTENANCE

No tools required for lamp and ballast access.

INSTALLATION

Suspension by chain, cable, hook or monopoint with appropriate accessories.

WARRANTY

One year limited warranty against defects in manufacturing. Visit tcpi.com for extension options.

LISTING

UL/cUL Listed—Suitable for damp locations.



Product Ordering Matrix (Order Lamps Separately)

Family	Ballast Cover	Lamp Quantity	Lamp Type	Voltage	Ballast Factor	Ballast Options*	Options
GP4 - 4' General Purpose Strip	SA - Specular Aluminum	1 (4' Fixture Only)	32 - (T8 25-32W)	UNI - (120-277)	H - (T8 High)	PRS - (Program Rapid Start)	(See Below)
GP8 - 8' General Purpose Strip	WA - White Aluminum	2 (4' or 8' Fixture)	54 - (T5HO 54W)	347	N - (T8 Normal)	DIM - (Dimming)	
		4 (8' Fixture Only)		480 - T5 only	L - (T8 Low)		
				480X - Step Down	V - (T5HO)	*UNI and Step Down only	

OPTIONS (Add to catalog number in order shown)

1 Power Cords

- 6C** - 6' PCord 300V 16/3 SJTOW NO PLUG
- 6C4** - 6' PCord 300V 18/4 SJTOW NO PLUG
- 6W** - 6' WHIP PCord 600V 16/3 NO PLUG
- 2P** - 8' PCord 125V 15A 16/3 SJTOW NEMA 5-15P
- 3P** - 8' PCord 125V 15A 16/3 SJTOW NEMA L5-15P
- 8T** - 8' PCord 480V 20A 16/3 SEOW NEMA L8-20P
- 9T** - 8' PCord 250V 20A 16/3 SJTOW NEMA L6-20P
- 4T** - 10' PCord 125V 20A 16/3 SJTOW NEMA L5-20P
- 10T** - 10' PCord 277V 15A 14/3 SJTOW NEMA L7-15P
- 10T2** - 10' PCord 277V 20A 14/3 SJTOW NEMA L7-20P
- 10C** - 10' PCord 277V SJTOW NO PLUG
- 10C6** - 10' PCord 600V 15A 16/3 STOW NO PLUG
- 20C** - 20' PCord 277V 20A 16/3 SJTOW NO PLUG
- 20C4** - 20' PCord 300V 18/4 SJTOW NO PLUG

2 Occupancy Sensors

- TS1** - TCP Occupancy Sensor w/bracket and interchangeable lenses, 40' or less, 120V, 277V, or 347V.
- TS1C** - TCP Cold Storage Occupancy Sensor w/bracket and interchangeable lenses, 40' or less, 120V, 277V, or 347V.
- TS4** - TCP Occupancy Sensor w/bracket and interchangeable lenses, 40' or less, 480V.
- TS4C** - TCP Cold Storage Occupancy Sensor w/bracket and interchangeable lenses, 40' or less, 480V.

Use a program rapid start ballast with occupancy sensor. TCP is not responsible for lamps failing prematurely due to an occupancy sensor being used with an instant start ballast.

3 Emergency Ballasts

- 20B1** - TCP 450 LMS 90 min (T8)
- 20B6** - TCP 700 LMS 90 min (T8)
- 20B5** - TCP 1400 LMS 90 min (T8 or T5)
- 20BL5** - TCP 800 LMS 90 min (T5)
- 20BL6** - TCP 1350 LMS 90 min (T5)

Emergency Ballast Notes:

Orders with an emergency ballast must include a note on the order indicating the number of lamps to be operated, which lamp(s) will be operated by the emergency ballast (i.e. 3rd lamp), and what voltage is to be used (i.e. 120V). See Emergency Ballast Spec Sheets for details.

4 Special Mounting

- HCB** - Hub Connector Box - 3/4" Threaded Hub Mount

AVAILABLE HANGING KITS (ordered separately)

- EZHANGER** - 15' adjustable Aircraft Cable Hanging Kit
- LHKIT** - Single Point Hook Mounting Kit complete

† If a desired lamp and/or ballast is needed in a TCP linear fluorescent fixture, please provide a spec sheet when consulting with your local sales rep. The sales rep will provide a price for the desired lamp and/or ballast.