

Features & Benefits

Illumination

- Long life, efficient, ultra bright white LED lamp heads
- 1.0 watt (8 LEDs x 0.125W) per head
- High performance, chrome-plated metallized reflector and plastic lens for optimal light distribution
- Two adjustable LED lamp heads provide optimal center-to-center spacing

Electrical

- Dual 120/277 voltage standard
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- 3.6V long life, maintenance-free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours

Mounting

- Universal knockout pattern on back plate for surface mount. Snaps into place making internal electrical connections.
- Suitable for wall or ceiling mount.
- Knockout for conduit applications.

Housing


- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white.

Warranty/Listing

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (32°F to 104°F)



Dimensions



Ordering Information

Item #	Description	LED Color	Housing Color
LED21760A	LED Adjustable Optics Emergency Light	White	White

Specifications and dimensions subject to change without notice.