



LED HID Series

DIRECTIONAL · 50,000 HOURS · 120-277 VAC

TCP's LED T-shape HID replacements are changing the LED game for HID replacement lamps. Unlike traditional HID and LED "Corn Cob" solutions, the TCP LED T-shapes are directional and deliver maximum lumens on the floor. The plastic lens helps to minimize glare and increase overall lamp performance.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Street Lights
- Roadways
- Landscape Lighting

- Parking Lots
- Warehouses
- Industrial Lighting

FEATURES	BENEFITS
Operates on less energy than traditional metal halide products	Instant energy savings
Long life – 50,000 hours	Minimizes replacement and maintenance costs
Directional 180° beam angle	Delivering maximum lumens distribution on the floor
Shatter resistant	Lower risk of injury and breakage
Isolated driver	All for better heat dissipation
Wet location rated	Suitable for wet locations—when exposed to water use only with device base up
Approved for totally enclosed surface luminaires	Can be used in both open and enclosed fixtures

SPECIFICATIONS

Color Temperatures	4000K, 5000K
Wattage Replacements	
Input Line Voltage	120-277 VAC
Input Line Frequency	50/60HZ
Lamp Life (Rated)	50,000 hours
Minimum Starting Temp	22°C
Maximum Operating Temp	
CRI	





5 YEAR WARRANTY

* Based on 12 hours use per day

Non Dimmable















DIRECTIONAL • 50,000 HOURS • 120-277 VAC

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	ССТ	COLOR TEMP	BEAM ANGLE	MOL (inches)	DIA (inches)	WEIGHT (pounds)	BASE	MASTER PACK
90W LED HII														
LHID25040*	LED 90W MH400 EX39 40K	120-277V	90	250-400	13,600	151.11	>80	4000K	180°	10.3	5.2	2.4	EX39	6
LHID25050*	LED 90W MH400 EX39 50K	120-277V	90	250-400	13,600	151.11	>80	5000K	180°	10.3	5.2	2.4	EX39	6
65W LED HII														
LHID17540*	LED 65W MH250 EX39 40K	120-277V	65	175-250	9900	152.31	>80	4000K	180°	10.3	5.2	2.0	EX39	6
LHID17550*	LED 65W MH250 EX39 50K	120-277V	65	175-250	9900	152.31	>80	5000K	180°	10.3	5.2	2.4	EX39	6
40W LED HII														
LHID15040	LED 40W MH175 E26 40K	120-277V	40	150-175	5850	146.25	>80	4000K	180°	8.5	4.4	1.4	includes E26 to E39 ADAPTER	6
LHID15050	LED 40W MH175 E26 50K	120-277V	40	150-175	5850	146.25	>80	5000K	180°	8.5	4.4	1.4	includes E26 to E39 ADAPTER	6
25W LED HII														
LHID10040	LED 25W MH150 E26 40K	120-277V	25	100-150	3750	150.00	>80	4000K	180°	7.4	3.8	1.1	E26	6
LHID10050	LED 25W MH150 E26 50K	120-277V	25	100-150	3750	150.00	>80	5000K	180°	7.4	3.8	1.1	E26	6

^{*} DLC approved.





5 YEAR
WARRANTY
Based on 12 hours use per day

LED T-shape HIDs and traditional LED HIDs "Corn Cob" COMPARISON







For the most up-to-date specs, please visit www.tcpi.com




LED T-shape HIDs and traditional LED HIDs "Corn Cob"

COMPARISON continued

BY ZONE LHID250 ZONAL LUMENS 90w TL 100w CC


Candela Display



1 CTL 4976 L100MHX39... - Vertical Plane Through Horizontal Angles (225 - 45) Max. Candela # 2 CTL 4973 LHID25... - Vertical Plane Through Horizontal Angles (247.5 - 67.5) Max. Candela

BY ZONE LHID150 **ZONAL LUMENS**

Candela Display



1 CTL 4971_LHID15... - Vertical Plane Through Horizontal Angles (337.5 - 157.5) Max. Candela # 2 CTL 4975_L45MHE... - Vertical Plane Through Horizontal Angles (270 - 90) Max. Candela

For the most up-to-date specs, please visit www.tcpi.com



TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market—that transforms your surroundings and envelopes you in warmth—lighting that generates beauty with every flip of the switch.

