

LED LAMP ARTISAN



A19, A15, B10, ST19, G Series

**MILKY
WHITE**

**LOW
non visible
FLICKER**

UL LISTED US FC RoHS COMPLIANT

Features & Benefits

Reduced flicker down to 10%

- Compare to 6.6% traditional incandescent
- Far below California T20 standard 30%
- Significantly improve light quality
- Optimize eye comfort

Milky white glass cover

Dimmable, High CRI (80+)

15,000 hour average life span


Rated for damp locations

Warranty & Cautions

2-year limited warranty

Operating temperature range between -20°C and +40°C

Dimensional drawing



Ordering Information

Example: AR-A15LF/5W/30/D/MW

LED CLASS	LAMP TYPE	WATTAGE	CCT(K)	BASE	DIMMABLE	COVER
AR (Artisan)	A15LF, A19LF B10LF ST19LF G16.5LF, G30LF, G40LF	4W 5W 8W	30 (3000K)	E12 (E12) Blank (E26)	D (dimmable)	MW (Milky White)

Product Specification

Ordering Code	Model Number	Product Description	Watts (W)	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens (lm)	CCT(K)	CRI	Damp LOC.	M.O.L. (inch)	Case QTY.
1771213	AR-A15LF/5W/30/D/MW	A15 Low Flicker 5W 30K Dimmable Milky White	5	60W	E26	120	15,000	330°	450	3000	80	Y	3.54	60
1772205	AR-A19LF/8W/30/D/MW	A19 Low Flicker 8W 30K Dimmable Milky White	8	60W	E26	120	15,000	330°	750	3000	80	Y	4.29	20
1771214	AR-ST19LF/5W/30/D/MW	ST19 Low Flicker 5W 30K Dimmable Milky White	5	60W	E26	120	15,000	330°	450	3000	80	Y	5.39	50
1771211	AR-B10LF/4W/30/E12/D/MW	B10 Low Flicker 4W 30K Dimmable Milky White	4	40W	E12	120	15,000	330°	280	3000	80	Y	3.78	50
1771212	AR-G16.5LF/4W/30/E12/D/MW	G16.5 Low Flicker 4W 30K Dimmable Milky White	4	40W	E12	120	15,000	330°	300	3000	80	Y	3.31	50
1771216	AR-G30LF/5W/30/D/MW	G30 Low Flicker 5W 30K Dimmable Milky White	5	50W	E26	120	15,000	330°	450	3000	80	Y	5.28	40
1771218	AR-G40LF/4W/30/D/MW	G40 Low Flicker 4W 30K Dimmable Milky White	4	40W	E26	120	15,000	330°	320	3000	80	Y	6.77	8