

LED LAMP

HD Series



LED MR16 Bulbs HD-MR16



15,000hrs: 2-year; 25,000hrs: 3-year limited warranty

Operating temperature range -20 °C ~ +45 °C



MR16/JDR

MR16/GU5.3

Features & Benefits

cULus, Energy Star listed

High CRI (90+)*, Low flicker*

Dimmable


25,000 hrs average life*

Suitable for use in totally enclosed luminaires

Damp location approved

*For applicable models, see product specification below

Dimensional Drawing



Ordering Information Example: HD-MR16/9W/30/SP15/GU5.3/D/HL

Family Name	Lamp Type	Wattage	CCT(K)	Beam Angle	Base	Dimmable	Others
HD	MR16 MR16LF (Low flicker)	6.5W 8W 9W	30 (3000K) 40 (4000K)	SP15 (15°) FL25 (25°) WFL35 (35°)	JDR (E26) GU5.3	D (dimmable)	HL (High lumen) I90 (CRI 90)

Product Specification

Ordering Code	Energy Star	Model Number	Wattage (W)	Replacement Incandescent	Base	Voltage (V)	Hour Rating	Beam Angle	Initial Lumens(lm)	CCT(K)	CRI	C.B.C.P	Enclosed Fixture Application	Damp LOC.	M.O.D. (inch)	M.O.L. (inch)	Case QTY.
1782229	Yes	HD-MR16LF/9W/8W/30/FL35/GU5.3/D/HL "low flicker"	8	50W	GU5.3	12	15,000	35°	595	3000	90	1463	Y	Y	1.97	1.87	50
1782225	Yes	HD-MR16/9W/30/SP15/GU5.3/D/HL	9	60W	GU5.3	12	25,000	15°	685	3000	80	6800	Y	Y	1.97	1.87	50
1782226	Yes	HD-MR16/9W/30/FL25/GU5.3/D/HL	9	60W	GU5.3	12	25,000	25°	685	3000	80	3200	Y	Y	1.97	1.87	50
1782227	Yes	HD-MR16/9W/30/FL35/GU5.3/D/HL	9	60W	GU5.3	12	25,000	35°	685	3000	80	1850	Y	Y	1.97	1.87	50
1762810	Yes	HD-MR16/6.5W/40/FL35/JDR/D	6.5	40W	E26	120	25,000	35°	500	4000	80	1346	Y	Y	1.97	2.3	50