

LED Area Light



SSL-AL3

Segment	Wattage Range	Lumen Range
Commercial & Industrial	Selectable Wattage (70-500W)	9,100-65,000lm

Features

- Slim & Compact LED Area Lighter with Polycarbonate Lens.
- IP65 Wet Location rated with operating temperature range of -40°C ~ $+45^{\circ}\text{C}$.
- Field Selectable (CCT 3000K, 4000K & 5000K) and wattage of 70 – 500 W
- Efficacy of $\geq 130\text{ lm/W}$ with Lumiled LED
- 120-347V LED Auto-Sensing driver with 10KV Surge Protection Device.
- CRI > 80 , L70 @ 50,000 Hrs.

Specifications

Housing:

Pressure Die Cast Aluminum body to ensure better Thermal Management.

Optics:

UV Resistant Prismatic Polycarbonate Lens Type III, optional Type IV and V ordered separately.

Mounting:

Multiple installation via. Slipfitters, Square/Round Pole Mount, Adjustable Trunnion & Small Yoke.

Driver:

Auto-sensing 120-347 V LED driver with Operating temperature range of -40°C ~ $+45^{\circ}\text{C}$


LED:

Field Selectable CCT of 3000K, 4000K & 5000K. Efficacy of $\geq 130\text{ lm/w}$.

Controls:

Compatible with 0-10V Dimming. Area light is complete with installed photocell receptacle and "Shorting Cap" for ease of photocell application if desired. Photocell is an option and sold separately.

Dimensional Drawing



	L	L2	W	H
AL3/T3/150S	13.31"	11.41"	12.4"	2.47"
AL3/T3/300M	19.19"	17.27"	12.4"	2.48"
AL3/T3/500L	27.33"	25.44"	13.21"	2.86"



AL3/T3/150S




AL3/T3/300M



AL3/T3/500L



Polar Candela



Applications



Roadways



Parking Lots



Auto Dealerships



Campuses

LED Area Light



SSL-AL3	Segment	Wattage Range	Lumen Range
	Commercial & Industrial	Selectable Wattage (70-500W)	9,100-65,000lm

Ordering Information Example: SSL-AL3/T3/150S/MW/MK/120-347V/DB/D/SCR

Family Name	Fixture Type	Light Distribution Type	Wattage	CCT	Voltage	Body Finish	Dimmable	Others	Accessories
SSL (Solid state lighting)	AL3 (LED area light)	T3 (Type III)*	150S/MW (Max.150W, Selectable Wattage) 300M/MW (Max.300W, Selectable Wattage) 500L/MW (Max.500W, Selectable Wattage)	MK (Selectable CCT) 50 (5000K)	120-347V	DB (Dark Bronze) BK (Black)	D (0-10V Dimming)	SCR (Shorting cap receptacle)	SSL-AL3/SSF-MTG SSL-AL3/SQ-RD-POLE-MTG SSL-AL3/TRUN-MTG SSL-AL3/YOKES-MTG SSL-AL3/120-347V/PC SSL-AL3/SC SSL-AL3/T4-S/LENS SSL-AL3/T5/LENS SSL-AL3/HS

* Type III is default, you can order the optional lens separately for type V (T5) and type IV (T4).

Product Information

Ordering Code	Model Number	Wattage (W)	Body Finish	Input Voltage (V)	Hour Rating	Optics/ Distribution	Initial Delivered Lumens (lm)	CCT (K)	CRI	Wet Location	Dimension LxWxH - L2 (inch)	Case QTY.
3680363	SSL-AL3/T3/150S/MW/MK/120-347V/DB/D/SCR	150-100-70	Dark Bronze	120-347	50,000	Type III	19500-13000-9100	30-40-50	80	Y	13.31 X 12.4 X 2.47 - 11.41	1
3680364	SSL-AL3/T3/150S/MW/MK/120-347V/BK/D/SCR	150-100-70	Black	120-347	50,000	Type III	19500-13000-9100	30-40-50	80	Y	13.31 X 12.4 X 2.47 - 11.41	1
3680365	SSL-AL3/T3/300M/MW/MK/120-347V/DB/D/SCR	300-240-200	Dark Bronze	120-347	50,000	Type III	39000-31200-26000	30-40-50	80	Y	19.19 X 12.4 X 2.48 - 17.27	1
3680366	SSL-AL3/T3/300M/MW/MK/120-347V/BK/D/SCR	300-240-200	Black	120-347	50,000	Type III	39000-31200-26000	30-40-50	80	Y	19.19 X 12.4 X 2.48 - 17.27	1
3680367	SSL-AL3/T3/500L/MW/50/120-347V/DB/D/SCR	500-450-400	Dark Bronze	120-347	50,000	Type III	65000-58500-52000	5000	80	Y	27.33 X 13.21 X 2.86 - 25.44	1
3680368	SSL-AL3/T3/500L/MW/50/120-347V/BK/D/SCR	500-450-400	Black	120-347	50,000	Type III	65000-58500-52000	5000	80	Y	27.33 X 13.21 X 2.86 - 25.44	1
3660221	SSL-AL3/SSF-MTG/DB	SSL-AL3, Adjustable Slipfitter for Area Lighter, Dark Bronze										
3660222	SSL-AL3/SSF-MTG/BK	SSL-AL3, Adjustable Slipfitter for Area Lighter, Black										
3660223	SSL-AL3/SQ-RD-POLE-MTG/DB	SSL-AL3, Square/Round Pole Mount, Adjustable for Area Lighter, Dark Bronze										
3660224	SSL-AL3/SQ-RD-POLE-MTG/BK	SSL-AL3, Square/Round Pole Mount, Adjustable for Area Lighter, Black										
3660225	SSL-AL3/TRUN-MTG/DB	SSL-AL3, Adjustable Trunnion Mount for Area Lighter, Dark Bronze										
3660226	SSL-AL3/TRUN-MTG/BK	SSL-AL3, Adjustable Trunnion Mount for Area Lighter, Black										
3660227	SSL-AL3/YOKES-MTG/DB	SSL-AL3, Yoke S (Small) Fits 150S & 300M Series Mount for Area Lighter, Dark Bronze										
3660228	SSL-AL3/YOKES-MTG/BK	SSL-AL3, Yoke S (Small) Fits 150S & 300M Series Mount for Area Lighter, Black										
3660231	SSL-AL3/120-347V/PC	SSL-AL3, 120-347V Photocell Sensor										
3660232	SSL-AL3/SC	SSL-AL3, Shorting Cap										
3660233	SSL-AL3/T4-S/LENSSM	SSL-AL3, Type 4 (IV-S) Lens, 1 S (Small) only required for 150M change and 2 M (Medium) needed for 300L Series										
3660234	SSL-AL3/T4-S/LENSL	SSL-AL3, Type 4 (IV-S) Lens, 1 L (Large) only required for 500L Series										
3660235	SSL-AL3/T5/LENSSM	SSL-AL3, Type 5 (V) Lens, 1 S (Small) only required for 150M change and 2 M (Medium) needed for 300L Series										
3660236	SSL-AL3/T5/LENSL	SSL-AL3, Type 5 (V) Lens, 1 L (Large) only required for 500L Series										
3660237	SSL-AL3/HS/DB	SSL-AL3, House Shield, 1 HS for wattages 150S, 2 HS for wattages 300L, Area Lighter, Dark Bronze										
3660238	SSL-AL3/HS/BK	SSL-AL3, House Shield, 1 HS for wattages 150S, 2 HS for wattages 300L, Area Lighter, Black										

Accessories

SSL-AL3/SSF-MTG	SSL-AL3/SQ-RD-POLE-MTG	SSL-AL3/TRUN-MTG	SSL-AL3/YOKES-MTG	SSL-AL3/120-347V/PC	SSL-AL3/SC	SSL-AL3/T4-T5/LENS	SSL-AL3/HS

Related Products

SSL-MFL	SSL-WP1TS	SSL-XHC2	DL-VT2