



LED FIXTURE

SSL Series

LED High Bay SSL-UHB

LED High Bay Lighting Fixture with Magnesium Alloy heatsink



Features & Benefits

cETC listed, DLC Premium

System light efficacy 130 LPW

Magnesium Alloy material, lighter in weight

Tilted heat sink back design for easy wash-off

Superior electrical and thermal conductivity

Durable TGIC painting **White** finish, better for tough weather conditions

10 ft power cord

LG LED Chip

CRI $\geq$ 80, L70@ 100,000 Hrs

Voltage 120-277V and 347/480V

120° Beam spread

1-10V dimming

IP65 rated, wet location

Warranty


5-year limited warranty in commercial use from the date of purchase

Operating temperature range between -40°C and +50°C


Applications

Warehouse/Manufacturing Facilities, Convention Centers/Sporting Arenas
Big-Box Retail Stores, Cold Storage Facilities, Gymnasiums


Dimensional drawing




100W




150W



200W



240W



	DIA	H
100W	9.65"	7.24"
150W	11.02"	7.95"
200W	11.81"	8.23"
240W	11.81"	8.23"

LED High Bay

SSL-UHB

Ordering Information Example: SSL-UHB/100W/50/UNV/HK/D

Family Name	Fixture Type	Wattage	CCT	Voltage (V)	Mounting	Dimmable	Options
SSL (Solid State Lighting)	UHB (Universal High Bay)	100W 150W 200W 240W	50 (5000K)	UNV (120-277V) HVV (347/480V)	HK (Hook Mounting)	D (1-10V dimming)	SSL-UHB/14/AL/HOOD/90D SSL-UHB/16/PC/HOOD/70D SSL-UHB/PC/DIFFUSER/17UP SSL-UHB/JBOX SSL-UHB/SENSOR SSL-UHB/IP65JBOX



HK (Hook Mounting)

Product Specification

Ordering Code	DLC (Premium)	Model Number	Wattage (W)	Input Voltage (V)	Hour Rating	Initial Delivered Lumens (lumen)	CCT (K)	CRI	Dimension DIA×H(inch)	Case QTY.
3666123		SSL-UHB/100W/50/UNV/HK/D	100	120-277V	100,000	13,000	5000	≥80	9.65×7.24	1
3666228		SSL-UHB/100W/50/HVV/HK/D	100	347/480V	100,000	13,000	5000	≥80	9.65×7.24	1
3667115	Y	SSL-UHB/150W/50/UNV/HK/D	150	120-277V	100,000	19,500	5000	≥80	11.02×7.95	1
3667217	Y	SSL-UHB/150W/50/HVV/HK/D	150	347/480V	100,000	19,500	5000	≥80	11.02×7.95	1
3667116	Y	SSL-UHB/200W/50/UNV/HK/D	200	120-277V	100,000	26,000	5000	≥80	11.81×8.23	1
3667218	Y	SSL-UHB/200W/50/HVV/HK/D	200	347/480V	100,000	26,000	5000	≥80	11.81×8.23	1
3667129	Y	SSL-UHB/240W/50/UNV/HK/D	240	120-277V	100,000	34,800	5000	≥80	11.81×8.23	1
3667231	Y	SSL-UHB/240W/50/HVV/HK/D	240	347/480V	100,000	34,800	5000	≥80	11.81×8.23	1
3660041		SSL-UHB/14/AL/HOOD/90D	90 Degree 14" Aluminium Hood							
3660042		SSL-UHB/16/PC/HOOD/70D	70 Degree 16" Polycarbonate Hood							
3660043		SSL-UHB/PC/DIFFUSER/17UP	180 Degree Polycarbonate Diffuser w/ 17% up light.							
3660044		SSL-UHB/JBOX	Junction Box for Conduit Mtg, Through Wiring, White Finish							
3660045		SSL-UHB/SENSOR	Sensor, 120-277V, Daylight & Motion sensing.							
3660046		SSL-UHB/IP65JBOX	IP65 Junction Box (use with Sensor) applications.							



90° Aluminium Reflector
SSL-UHB/14/AL/HOOD/90D



70° PC Reflector
SSL-UHB/16/PC/HOOD/70D



180° PC Lens
SSL-UHB/PC/DIFFUSER/17UP



Junction Box
SSL-UHB/JBOX



Sensor
SSL-UHB/SENSOR



Junction Box (use with sensor)
SSL-UHB/IP65JBOX