

LED LAMP

VIVID Series

Bypass T5 Lamp



VIV-T5BPSP4



Features & Benefits

DLC approved, Frost PET Film, Shatter Protect ¹	120-277V & 347V*, 50000 hour life (L70)
External ballast not required	NSF/ANSI 2 certified**
Double-ended installation	Suitable for splash zones of food equipment
Replaces T5 HO & T5 HE	Our safety features allow for installation as well as misapplication protection ²
180° Beam angle, High CRI (83+)	

¹ ShatterProtect utilizes PET film to reduce the unexpected risk of shattering

*For applicable models, see product specification below

**Need to work with NSF certified lighting fixtures

²Contact your local Turolight representative for detail

Dimensional drawing



Warranty & Cautions

5-year limited warranty for DLC listed lamps

Operating temperature range between -20°C and +45°C

Product Specification

Ordering Code	DLC	Model Number	Wattage (W)	Voltage (V)	Base	Hour Rating	Beam Angle	Initial Lumen (lm)	CCT(K)	CRI	M.O.L. (inch)	Case QTY.
Replace T5 HO 120-277V												
1754200	Y	VIV-T5BPSP4/25W/30/F (4FT HO)	25	120-277	G5	50,000	180	3200	3000	83	46	25
1754300	Y	VIV-T5BPSP4/25W/35/F (4FT HO)	25	120-277	G5	50,000	180	3200	3500	83	46	25
1754402	Y	VIV-T5BPSP4/25W/40/F (4FT HO)	25	120-277	G5	50,000	180	3300	4000	83	46	25
1754500	Y	VIV-T5BPSP4/25W/50/F (4FT HO)	25	120-277	G5	50,000	180	3400	5000	83	46	25
Replace T5 HO 347V												
1754201	Y	VIV-T5BPSP4/25W/30/F/347V (4FT HO)	25	347	G5	50,000	180	3200	3000	83	46	25
1754301	Y	VIV-T5BPSP4/25W/35/F/347V (4FT HO)	25	347	G5	50,000	180	3200	3500	83	46	25
1754403	Y	VIV-T5BPSP4/25W/40/F/347V (4FT HO)	25	347	G5	50,000	180	3300	4000	83	46	25
1754501	Y	VIV-T5BPSP4/25W/50/F/347V (4FT HO)	25	347	G5	50,000	180	3400	5000	83	46	25
Replace T5 HE												
1752216	Y	VIV-T5BPSP4/13W/30/F (4FT HE)	13	120-277	G5	50,000	180	1600	3000	83	46	25
1752305	Y	VIV-T5BPSP4/13W/35/F (4FT HE)	13	120-277	G5	50,000	180	1600	3500	83	46	25
1752413	Y	VIV-T5BPSP4/13W/40/F (4FT HE)	13	120-277	G5	50,000	180	1650	4000	83	46	25
1752509	Y	VIV-T5BPSP4/13W/50/F (4FT HE)	13	120-277	G5	50,000	180	1700	5000	83	46	25

Double-ended Wiring

