


# 100W LED Temporary Work Lighting

Order Code: SM20896





Physical Characteristics	
Input Cable Length	9' (3m)
Overall Length A	14.9" (378.5 mm)
Diameter B	6.7" (170 mm)
Weight	3.0 lbs (1.36 kg)
Mounting Thread	M10 (Course Thread)

Electrical Characteristics	
Input Voltage Range	120V, 1A, 50/60Hz
Driver	Internal within lamp
Power Factor	>0.90
THD	<20%
Plug and Receptacle	NEMA 5-15 Straight Blade
Receptacle Rating	11A Max
Max Fixtures Per String	11

Regulatory Qualifications
UL Listed
IP Rating: IP64



### Description

Venture Lighting's temporary lighting luminaires are durable, light weight, and hook mounting options allows for easy installation and movement. These LED luminaires are designed to be dependable and quickly and easily installed. Each fixture is linkable via the integrated receptacle.

## **Applications**

- · Construction sites
- · Warehouses, factories and workshops
- · Highway toll stations and gas stations

# Construction

Each fixture is supplied with a protective cage around the fixture to protect the fixture from the harsh physical environment typical in temporary lighting applications. The LEDs are mounted to a custom extruded heat sink which allows for proper thermal management of the light sources. The luminaires are IP64 rated (suitable for damp locations).

#### Electrical


The power supply accepts 120V 60 Hz input. The luminaires are IP64 rated. Each fixture is supplied with a 9 foot long cable with a NEMA 5-15 straight blade plug.


#### Mounting

The fixture is provided with a versatile hook mount (carabiner style) which can be mounted to numerous field applications.



# Venture 100W LED Temporary Work Lighting





**Photometry** 

(800) 451-2606 Fax: (800) 451-2605 7905 Cochran Rd, Suite 300 Glenwillow, Ohio 44139  $\hbox{E-mail: Venture\_Lighting@VentureLighting.com}\\$ VentureLighting.com

