



200W LED Highbay Fixture

Order Code: HB22920



Description

Venture Lighting's Modern Highbay luminaires are low profile, durable, and designed for long life and low maintenance. They are designed to quickly and easily upgrade existing H.I.D and fluorescent fixtures.

Construction

The high performance LED source is mounted to an aluminum heat sink which is designed to ensure proper thermal management of the system. This design allows for a cooler running LED chip which leads to longer lifetime, better efficacy, and color consistency. Fixtures are rated for an ambient operating temperature range -30°C to 40°C. Modern high bay luminaires are water and dust resistant, with IP65 rating.

Optics

The 200W units are equipped with a 90 degree beam spread for higher mounting heights and are also field adjustable with an accessory lens.

Electrical

The power supply has a range of 120-277V, 50/60 Hz. 0-10V DC dimming capability is standard. The luminaire is rated for damp and dry locations.

DLC Model# HW-200C8-AB

Product Performance

Wattage	200W
Lumen Output	26000
Correlated Color Temperature (CCT)	5000K
Color Rendering Index (CRI)	80
Lumen Maintenance @50,000 hours*	92%
Calculated L70 @ 25°C Ambient in Hours*	223,000
Replaces HID Wattage	750W
Spacing Criterion (0-180)	1.3 x mtg height
Spacing Criterion (90-270)	1.3 x mtg height
Beam Angle (°)	90°
Operating Temperature Range	-22°F to 104°F (-30°C to 40°C)

Physical Characteristics

Input Cable Length	5ft.
Safety Cable Length	3ft.
Fixture Color	White
Weight	16.1 lbs
Length	15.1" dia.
Height	8.1"

Electrical Characteristics

Amperage Draw (Input Volts/Amps)	120/1.69 208/0.97 240/0.85 277/0.73
Surge Protection	4kV

Regulatory Qualifications

cULus Listed / DLC Qualified - Model# HW-200C8-AB

Accessories

RF13912 - 16.5" Dia. Acrylic Reflector for 100W to 300W Highbay
RF13388 - 15.3" Dia. Alum. Shield for 100 to 300W Highbay (Silver)
LN13632 - 120 Degree Plastic Flat Lens for 100W to 300W Highbay
LN28431 - 50 Degree Lens for 100W-200W Modern HB (except 200W High Temp.)
AC78196 - 150W-200W Pendant Mount Kit (White) for ¾" NPT
LN13421 - 120 degree Glass lens for 100 to 300W Modern highbays
Add suffix "-S1" to order code for a factory installed fixture with a MOTION ONLY Sensor part # PH41623
Add suffix "-S2" to order code for a factory installed fixture with a MOTION/DIM/PHOTOCELL Sensor part # PH77409
Add suffix "-S3" to order code for a factory installed fixture with a WET & LOW TEMP. RATED MOTION ONLY Sensor (Part # PH21458)
Add suffix "-S4" to order code for a factory installed fixture with a WET & LOW TEMP. RATED MOTION/DIM/PHOTOCELL Sensor (Part # PH27419)
For factory installed plug options see below
For plug options see accessories tab (NOT FACTORY INSTALLED)


NOTE:

*Lumen maintenance data is based on LED testing per IESNA LM-80-08 and projected per IESNA TM-21-11



VENTURE
LIGHTING

Venture 200W LED Highbay Fixture



RF13912



RF13388



LN13632




LN28431



S1/S2 Factory Installed Sensor

Luminous Intensity Distribution Diagram



NEMA L5-15



NEMA L18-20P



NEMA L6-15



NEMA L7-15P

Plug Options*

"-P1" - NEMA L5-15P for 120V

"-P2" - NEMA L6-15P for 240V

"-P3" - NEMA L7-15P for 277V

"-P5" - NEMA L18-20P for 208V

Molded Plug Options with 11ft Cable*

"-P6-C" - NEMA L5-15P for 120V w/ Cable

"-P7-C" - NEMA L6-15P for 240V w/ Cable

"-P8-C" - NEMA L7-15P for 277V w/ Cable

"-P10-C" - NEMA L18-20P for 208V w/ Cable

NOTE: * Add Suffix to Part# for Factory Installed option

Factory installed plug options

(800) 451-2606
 Fax: (800) 451-2605
 2451 Enterprise Parkway East
 Twinsburg, Ohio 44087 USA
 E-mail: venture@adlt.com
VentureLighting.com

