



Description

Venture's LED Wrap fixture is a lightweight LED light fixture, designed for long life and low maintenance. The fixtures are designed to quickly and easily upgrade existing fluorescent fixtures.

Construction

The housing unit is constructed from heavy-duty aluminum. Fixtures are finished with a durable white polyester powder coating.

Electrical

The power supply has a range of 120-277V, 50/60 Hz. 0-10V DC Dimming is standard.

Mounting

Suitable for surface mount or pendant mount applications.

DLC Model# SM1-40NFA-01

Product Performance

Wattage	42W
Lumen Output	4280
Correlated Color Temperature (CCT)	4000K
Color Rendering Index (CRI)	80
Lumen Maintenance @50,000 hours*	89%
Calculated L70 @ 25°C Ambient in Hours*	143,000
Operating Temperature Range	-13°F to 104°F (-25°C to 40°C)

Physical Characteristics

Fixture Color	White
Weight	7 lbs
Width	6.5"
Length	48.7"
Height	2.54"

Electrical Characteristics

Amperage Draw (Input Volts/Amps)	120/0.36 208/0.21 240/0.19 277/0.16
----------------------------------	-------------------------------------

Regulatory Qualifications

cULus Listed

DLC Model# SM1-40NFA-01

Accessories

LN18124 - Replacement Acrylic Lens 4ft LED Wrap

NOTE:

*Lumen maintenance data is based on LED testing per IESNA LM-80-08 and projected per IESNA TM-21-11



Venture LED Wrap Fixture

(800) 451-2606
Fax: (800) 451-2605
2451 Enterprise Parkway East
Twinsburg, Ohio 44087 USA
E-mail: venture@adlt.com
VentureLighting.com

