

2x4 Volumetric Troffer

Order Code: TR51438

DLC Model# TB24-50NA-01



Description

Venture Lighting's LED Volumetric troffers are durable, long lasting, high quality, low maintenance lighting fixtures. Each are designed to be quick and easy upgrades to existing fluorescent fixtures.

Construction

The housing unit is constructed from heavy-duty aluminum. Fixtures are finished with a durable white polyester powder coating.

Electrical

The power supply has a range of 120-277V, 50/60 Hz. 0-10V dimming is standard. Rated for dry and damp locations.

Mounting

The fixture is designed for replacing fluorescent fixtures in T-grid drop ceiling

Product Performance	
Wattage	48W
Lumen Output	5970
Correlated Color Temperature (CCT)	4000K
Color Rendering Index (CRI)	80
Life Hours	50,000
Replaces Fluorescent Troffer	2x4
Operating Temperature Range	-13°F to 113°F (-25°C to 45°C)

Physical Characteristics	
Fixture Color	White
Weight	13.1 lbs
Width	23.7"
Length	47.7"
Height	2.7"

Electrical Characteristics	
Amperage Draw (Input Volts/Amps)	120/0.41 208/0.25 240/0.22 277/0.20

Regulatory Qualifications

cULus Listed, IC-Rated, Rated for dry and damp locations

DLC Model# TB24-50NA-01

Accessories

BB23468 - LED Fixture Battery Back-up

For a factory installed Battery Backup add "-EM" after order code (Lumens: 2870) - Temp Range: (0-50°C)†

LN17615 Replacement lens 2x4 Volumetric troffer

NOTE: †Operating temperature range for Battery Backup










Venture 2x4 Volumetric Troffer



(800) 451-2606 Fax: (800) 451-2605 2451 Enterprise Parkway East Twinsburg, Ohio 44087 USA E-mail: venture@adlt.com VentureLighting.com

