


60W LED Traditional Style Wallpack

Order Code: WP28195



Regulatory Qualifications



Fixture Color	Bronze
Weight	15 lbs
Width	14.2"
Length	7.63"
Height	9.25"

Electrical Characteristics	
Amperage Draw (Input Volts/Amps)	120/0.52 208/0.30 240/0.27 277/0.23

- 1	
	cULus Listed
	DLC Qualified - Model# WH2-060C-Axx
	Rated for wet location

716663301163
SP12714 – 120-277V Surge Protector
PH56903 - Button Photocell (120-277V)



Description

Venture Lighting's Wallpack luminaires are low profile, light weight, and designed for long life with low maintenance and great performance. These LED luminaires are designed to quickly and easilyupgrade existing HID wall pack fixtures.

Construction

Rugged die cast housing finished in a durable powder coat finish and with polycarbonate lens. The high performance LED sources are mounted to ensure proper thermal management of the system. The design allows for a cooler running LED chip which leads to longer lifetime, better efficacy, and color consistency. The fixture has a gasket sealed to eliminate the threat of contaminants damaging the components. The standard fixture color is bronze, custom colors available upon request.

Electrical

The power supply has a range of 120-277V, 50/60 Hz. The luminaires are rated for wet locations. Button photocell accessory can easily be mounted into the fixture. The Venture Lighting traditional style wallpack fixtures are not dimmable.

Mounting

Cast in template for wall mounting to a recessed junction box. The 120W Venture LED traditional style wallpack has the same footprint as 250W/320W/400W HID wallpacks.

NOTE:


*Lumen maintenance data is based on LED testing per IESNA LM-80-08 and projected per IESNA TM-21-11







Venture 60W LED Traditional Style Wallpack



(800) 451-2606 Fax: (800) 451-2605 2451 Enterprise Parkway East Twinsburg, Ohio 44087 USA E-mail: venture@adlt.com VentureLighting.com

