




### Technical data

| Product Code               |       | C3205 - Round-WH/BL/BN        | C3206 - Square - WH/BL |
|----------------------------|-------|-------------------------------|------------------------|
| Body Size                  | L(mm) | 90MM                          |                        |
|                            | H(mm) | 42MM                          |                        |
| LED Type                   |       | COB                           |                        |
| LED QTY (pcs)              |       | 1                             |                        |
| Beam angle                 |       | 24°                           |                        |
| Replacement Wattage(W)     |       | 60                            |                        |
| Dimmable                   |       | Y                             |                        |
| Input Voltage(V)           |       | 120V 60Hz                     |                        |
| Power (w)                  |       | 7W                            |                        |
| Luminous Flux              |       | >560Lm                        |                        |
| Color Temperature          |       | 2700K/3000K/3500K/4000K/5000K |                        |
| SDCM                       |       | <7                            |                        |
| CRI                        |       | >80                           |                        |
| Power Factor               |       | >0.9                          |                        |
| Lifetime (Hrs)             |       | 50000                         |                        |
| IC RATED:                  |       | Yes                           |                        |
| Certification Requirements |       | ETL                           |                        |



### Key Features

- Round & Square LED Downlight with integral driver in connection box
- Type IC Rated-no housing needed
- Multiple CCT
- Flexibility to switch color temperature during installation to suit a specific application, just adjust the color temperature with the slide switch
- Available shape: Round & Square
- Aluminium construction

### Dimensions

