

Combo Emergency Light



Housing

- . Injection-molded thermoplastic ABS housing.
- . Plastic enclosure with 5VA flame retardant
- . Two fully adjustable glare-free round shape light heads for emergency light
- . Single and double face universal.
- . Easy replacement pictogram design

Electrical

- . 120/347VAC Dual voltage operation
- . Test switch and charge LED indicator
- . 3.6V / 1000 Mah long-life, maintenance-free, rechargeable Ni-Cad battery
- . SMD 1.2W high power LED, CCT 6000K for emergency lamp heads
- . SMD 2835 LED, CCT 6000K for LED escape sign
- . Min 90 minutes discharge after charge battery 24 Hours

Limited Warranty:

This device complies with part 15 of FCC rules. Operation is subject to following 2 conditions:
1- This device may not cause harmful interference.
2 - This device must accept any interference received, including interference that may cause undesired operation.

Illumination

- . 1.2W per lamp head fixture provide 150lm output

Mounting

- . Suitable for wall mounting, ceiling mounting and side mounting
- . Housing snaps to canopy with simple twist and locking tightly Secure housing to canopy

Warranty/Listing

- . Three years warranty for battery
- . Five years warranty for electrical parts and housing
- . Suitable for use in 50°F (10°C) - 104°F (40°C) ambient temperature
- . CSA listed meets all requirement in C22.2 No.141-10, Suitable for Canada market

